

**NATIONAL ANNEX
TO
CYS EN 1993-4-3:2007 Eurocode 3: Design of steel
structures
Part 4-3: Pipelines**

Public Enquiry Draft

Period of Enquiry

November 19th 2007 to January 14th 2008

Readers are advised that this is a draft document and subject to change

**Prepared by: Eurocodes Committee
Ministry of Interior / Technical Chamber of Cyprus**

INTRODUCTION

This National Annex has been prepared by the Eurocodes Committee of the Technical Chamber of Cyprus which was commissioned by the Ministry of Interior of the Republic of Cyprus

NA 1 SCOPE

This National Annex is to be used together with CYS EN 1993-4-3:2007

This National Annex gives:

- (a) Nationally determined parameters for the following clauses of CYS EN 1993-4-3:2007 where National choice is allowed (see Section NA 2)
- 2.3 (2)
 - 3.2 (2)P, (3), (4)
 - 3.3 (2), (3), (4)
 - 3.4 (3)
 - 4.2 (1)P
 - 5.1.1 (2), (3), (4), (5), (6), (9), (10), (11), (12), (13)
 - 5.2.3 (2)
 - 5.2.4 (1)
- (b) Decisions on the use of the Informative Annexes A, B and C (see Section NA 3)
- (c) References to non-contradictory complementary information to assist the user to apply CYS EN 1993-4-3:2007. In this National Annex such information is provided for the following clauses in CYS EN 1993-4-3:2007 (see Section NA 4)
- None

NA 2 NATIONALLY DETERMINED PARAMETERS

NA 2.1 Clause 2.3 (2) Reliability differentiation

No minimum level of reliability for different types of pipelines is provided.

NA 2.2 Clause 3.2 (2)P Mechanical properties of pipeline steels

The value Δf is specified as $\Delta f = 50$ Mpa.

NA 2.3 Clause 3.2 (3) Mechanical properties of pipeline steels

The value $f_{u,min}/f_{y,min}$ is specified as $f_{u,min}/f_{y,min} = 1,1$.

NA 2.4 Clause 3.2 (4) Mechanical properties of pipeline steels

The value $\varepsilon_{u,min}$ is specified as $\varepsilon_{u,min} = 20$ %.

NA 2.5 Clause 3.3 (2) Mechanical properties of welds

The value x is specified as $x = 15$ %.

NA 2.6 Clause 3.3 (3) Mechanical properties of welds

The value ε is specified as $\varepsilon = 2$ %.

NA 2.7 Clause 3.3 (4) Mechanical properties of welds

The value y is specified as $y= 15 \%$.

NA 2.8 Clause 3.4 (3) Toughness requirements of plate materials and welds

The value z is specified as $z= 0,5 \%$.

NA 2.9 Clause 4.2 (1)P Partial factors for actions

No partial safety factors are provided.

NA 2.10 Clause 5.1.1 (2) Simplified calculation method for ultimate limit state design

The numerical values of γ_F are specified as follows: $\gamma_{F1}= 1,39$; $\gamma_{F2}= 1,50$; $\gamma_{F3}= 1,82$.

NA 2.11 Clause 5.1.1 (3) Simplified calculation method for ultimate limit state design

The values of D_e / t_{\min} are specified as follows: $\text{val240}= 70$; $\text{val360}= 80$; $\text{val415}= 92$; $\text{val480}= 106$.

NA 2.12 Clause 5.1.1 (4) Simplified calculation method for ultimate limit state design

The values of D_{cover} and G_{eff} are specified as follows: $D_{\text{cover}}= 2,5 \text{ m}$ and $G_{\text{eff}}= 65 \text{ kN/m}^2$.

NA 2.13 Clause 5.1.1 (5) Simplified calculation method for ultimate limit state design

The value of $t_{\text{spec,min}}$ is specified as $t_{\text{spec,min}}= 4,8 \text{ mm}$.

NA 2.14 Clause 5.1.1 (6) Simplified calculation method for ultimate limit state design

The values of d_s and ℓ are specified as follows: $d_s= 100 \text{ mm}$ and $\ell= 20 \text{ m}$.

NA 2.15 Clause 5.1.1 (9) Simplified calculation method for ultimate limit state design

The value of x is specified as $x= 20$.

NA 2.16 Clause 5.1.1 (10) Simplified calculation method for ultimate limit state design

The value of T is specified as $T= 35^\circ \text{ C}$.

NA 2.17 Clause 5.1.1 (11) Simplified calculation method for ultimate limit state design

The values of $T1$ and $T2$ are specified as follows: $T1= - 40^\circ \text{ C}$ and $T2= + 60^\circ \text{ C}$.

NA 2.18 Clause 5.1.1 (12) Simplified calculation method for ultimate limit state design

The values of y , $T3$, $D1$, $D2$ and l are specified as follows: $y= 20$; $T3= 20^\circ \text{ C}$; $D1= 300 \text{ mm}$; $D2= 450 \text{ mm}$ and $\ell= 2,0 \text{ m}$.

PUBLIC ENQUIRY DRAFT

National Annex to CYS EN 1993-4-3:2007 Eurocode 3: Design of steel structures
Part 4-3: Pipelines

NA 2.19 Clause 5.1.1 (13) Simplified calculation method for ultimate limit state design

The values of z , γ_F , D_2 and D_e / t_{\min} are specified as follows: $z= 20$; $\gamma_F= 1,82$; $D_2= 450$ mm; $\text{val}240= 57$; $\text{val}360= 61$; $\text{val}415= 70$; $\text{val}480= 81$.

NA 2.20 Clause 5.2.3 (2) LS3: Deformation

The value of x is specified as $x= 0,05$.

NA 2.21 Clause 5.2.4 (1) LS4: Fatigue

No other standards for fatigue loading are provided.

NA 3 DECISION ON USE OF THE INFORMATIVE ANNEXES A, B AND C

NA 3.1 Annex A

Annex A may be used

NA 3.2 Annex B

Annex B may be used

NA 3.3 Annex C

Annex C may be used

NA 4 REFERENCES TO NON-CONTRADICTORY COMPLEMENTARY INFORMATION

None